


**Gas Discharge Tubes**

**H4R30-600L**

**1: Applications**

- AC Power line L-N applications
- Class I and Class II Surge protection

**2: Dimension in mm**



## Specification of H4R30-600L

Nominal Dc spark-over voltage @ 100V/s	A-B >250V	
	B-C >600V	
	C-D >250V	
	A-D >800V	
Maximum impulse spark-over voltage @ 1KV/μs	A-B <800V	
	B-C <1500V	
	C-D <800V	
	A-D <2500V	
Response time	50ns	
Insulation resistance @DC100V	1GΩ	
Class I according to IEC 61643-11		
Max continuous operating voltage at 50/60 Hz	Uc	255V
Nominal discharge current 8/20μs	In	50KA
Impulse current 10/350μs	Iimp	30KA
Follow Current at 50/60Hz at 255V	If	1000A
Class II according to IEC 61643-11		
Max continuous operating voltage at 50/60 Hz	Uc	255V
Nominal discharge current 8/20μs	In	50KA
Maximum discharge current 8/20μs	Imax	100KA
Follow Current at 50/60Hz at 255V	If	1000A
Weight	~ 86g	
Delivery time	25days	
Voltage protection level	<2KV	
Quantity of electric charge	17.5As	
Quantity of electrodes	4PCS	
Marking, Green	R 600 YY	600 - Nominal voltage YY - Year of production

### 3:Application Figure



#### What can we do for our GDT?

- 1: We Can customize voltage: 500V,800V...etc
- 2: We Can developed low impulse GDT
- 3: We Can customize  $U_c, I_n, I_{max}, I_{lim}, I_f, TOV$ .
- 4: We Can developed cut off follow current 100A within 1 cycle when passing zero under AC260V(50Hz)
- 5: We Can customize multi-gap GDT used in DC or AC(L-N) over voltage protection
- 6: We Can customize GDT shape, marking, special Lead wire
- 7: We Can surpass our GDT competitors, help you pass the GDT test project & improve the GDT you currently use.
- 8: We can provide fast GDT delivery, Solve your GDT delivery time problem
- 9: We can help you analyze the competitor's parameters and tell you our perfect replacement GDT part number.