

Gas Discharge Tubes


H2R20S-600

1: Applications

- AC Power line N-PE applications
- Class I and Class II Surge protection



2: Dimension in mm



Specification of H2R20S-600

Dc spark-over voltage (100V/s)	1)	600V ±20%	
Front of wave spark-over voltage at 1.2/50us, 6KV		<1500V	
Breakdown time		<100ns	
- typical values		<20ns	
Insulation resistance @DC250V		10000MΩ	
Class I according to IEC 61643-11			
Max continuous operating voltage at 50/60 Hz	Uc	255V	
Nominal discharge current 8/20μs	In	40KA	
Impulse current 10/350μs	Iimp	20KA	
Class II according to IEC 61643-11			
Max continuous operating voltage at 50/60 Hz	Uc	255V	
Nominal discharge current 8/20μs	In	40KA	
Maximum discharge current 8/20μs	I _{max}	60KA	
capacitance at 1MHz		<6pF	
Weight		~ 5.2g	
UL 1449 Certification			
On the UL List			
Delivery time		20days	
Operation and storage temperature		-40℃ ... +90℃	
Marking, Blue	1) At delivery AQL 0.65 level II Military Standard 105E. 2) In ionized mode 3) DC Sparkover may exceed +/-30% ,but will continue to protect without venting Test according to ITU-T Rec. K.12	2R600 YY	600 - Nominal voltage YY - Year of production

3:Application Figure



What can we do for our GDT?

- 1: We Can customize voltage: 230V,500V,800V...etc
- 2: We Can developed low impulse GDT
- 3: We Can customize $U_c, I_n, I_{max}, I_{imp}, I_f, TOV$.
- 4: We Can developed cut off follow current 100A within 1 cycle when passing zero under AC260V(50Hz)
- 5: We Can customize multi-gap GDT used in DC or AC(L-N) over voltage protection
- 6: We Can customize GDT shape, marking, special Lead wire
- 7: We Can surpass our GDT competitors, help you pass the GDT test project & improve the GDT you currently use.
- 8: We can provide fast GDT delivery, Solve your GDT delivery time problem
- 9: We can help you analyze the competitor's parameters and tell you our perfect replacement GDT part number.